

IEEE Std 647™-2006(Revision of
IEEE Std 647-1995)

Errata to IEEE Standard Specification Format Guide and Test Procedure for Single-Axis Laser Gyros

Sponsor

Gyro and Accelerometer Panel Committee

of the

IEEE Aerospace and Electronic Systems Society

Copyright 2011 by the Institute of Electrical and Electronics Engineers, Inc. All rights reserved. Published 2011
Printed in the United States of America.

This correction sheet may be freely reproduced and distributed in order to maintain the utility and currency of the underlying Standard. This correction sheet may not be sold, licensed or otherwise distributed for any commercial purposes whatsoever. The content of this correction sheet may not be modified.

*Correction Sheet***Issued 9 December 2011**

Page 13, the content in 5.5.8 is a repeat of the content in 5.5.7, it should be deleted and the remainder of the subclauses renumbered as shown below:

5.5.8 Dielectric strength

5.5.9 Insulation resistance

5.5.10 Electromagnetic interference

5.5.11 Magnetic leakage

5.5.12 Electromagnetic compatibility

Page 15, subhead for 5.6.4 is absent it should read as shown below:

5.6.4 Environments

*Page 15, 5.6.4.1.1, the *g* in the sentence should be italicized to indicate gravity, not weight, as shown below:*

Sinusoidal: _____ [cm, in] DA (double amplitude) _____ to _____ Hz; _____ [m/s², *g*] peak, _____ to _____ Hz. Sweep rate: _____ min/octave (continuous). Exposure time: _____ [min, _____] per axis.

Page 42, 12.11.4, subclause citation should be corrected to read as 12.11.3 not 12.11.4, as shown below:

From the test data taken in 12.11.3 after the warm-up time, compute the combined anti-lock residual and quantization noise coefficient Q by forming the following Allan variance estimates: